

## Pull Model Internal Air Clamps Specifications

Size	Model	Weight	Length
8"	Wheel-Centering	120 lbs.	60"
10"	Wheel-Centering	175 lbs.	65"
12"	Wheel-Centering	190 lbs.	66"
12"-14"	Wheel-Centering	200 lbs.	66"

## Power-Travel Internal Air Clamp Specifications

Clamps 16" and larger are self-propelled. Powerful air motors drive the clamps forward through the pipe to the next joint.

Model No	Pipe Size		Length		Width		Height		Cube		Weight		Motor Propelled	Recommended Operating Air Pressure	
	IN.	MM.	IN.	M.	IN.	M.	IN.	M.	FT. <sup>3</sup>	M. <sup>3</sup>	LBS.	KGS.			
AC0800	8	203	56	1.4	8	0.2	12	0.3	3.1	0.1	300	136	No	90 – 110 lbs.	
AC1000	10	254	56	1.4	10	0.3	12	0.3	3.9	0.1	300	136	No		
AC1214	12	304	58	1.5	14	0.4	16	0.4	7.5	0.2	350	158	No	130 – 150 lbs.	
	14	355													
AC1618	16	406	81	2.1	18	0.5	20	0.5	16.9	0.5	575	261	No		
	18	457											Yes		
AC2022	20	508	90	2.3	22	0.6	24	0.6	27.5	0.8	750	340	Yes		
	22	558													
AC2426	24	609	107	2.7	26	0.7	28	0.7	45	1.3	1175	533	Yes		180 – 220 lbs.
	26	660													
AC2800	28	711	107	2.7	28	0.7	30	0.8	51.9	1.5	1250	567	Yes		
AC3032	30	762	110	2.8	32	0.8	34	0.9	69.2	1.9	1775	805	Yes		200 – 240 lbs.
	32	812													
AC3436	34	863	113	2.9	36	0.9	38	1.0	89.5	2.5	2100	952	Yes		
	36	914													
AC4042	40	1016	127	3.2	42	1.1	44	1.1	135.9	3.8	2625	1190	Yes		
	42	1066													
AC4648	46	1168	128	3.3	48	1.3	50	1.3	177.9	5.0	4375	1984	Yes		
	48	1219													
AC5660	56	1422	140	3.6	60	1.6	62	1.6	301.6	8.5	5700	2585	Yes		
	60	1524													

### C & L Pipeline Equipment Inc Quality

A full range of quality assurance and durability tests are conducted on each Internal Lineup Clamp prior to shipment.

All specifications and dimensions subject to change without notice.